

Kenttien mappaukset eri formaateista Finnan indeksiin

Mappings of fields from different record formats to Finna's main index

Main Index - Pääindeksi

See also the [authority index page](#).

Core Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3 (new organisations)	EAD2002 (old version)	LIDO	MARC				
id	Unique identifier	No	id, ids	recordID	recordID	recordID		eadheader- >eadid- >@identifier or eadheader- >eadid + ' ' + unitid- >@identifier or (ordinal number) Huom: mikäli käytetään 2- tasoista hierarkiaa (1. arkisto / arkistokokoelm a, 2. arkistoyksikkö) eadheader ja archdesc- elementtien id: t tulee olla samat: ead- >eadheader- >eadid == ead- >archdesc- >unitid	lidoRecID	001				
fullrecord	Original record data	No		record XML	record XML	record XML		record XML	record XML	record ISO2709 or XML				
allfields	All searchable information that doesn't fit into other searchable fields.	No	AllFields	(all fields)	(all fields)	all fields except 'format', 'id', 'identifier', 'date', 'dateCreate d', 'dateModifie d', 'filesize', 'inLanguage', 'position', 'recordID', 'rights', 'targetUri', 'uri'		(all fields)	SOLR fields: title, description, format, author, topic, material, measurements, identifier, culture	Fields 020, 024, 025, 026, 027, 028, 100 - 840, 856, 880, 900, 910, 911, 940, 952 and 979 except 300, 336 and 337 and subfields 6502, 856q and 979a				
fulltext	Full text	No	AllFields	-	-	-		-	-	-				
Institutional Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
institution	Institution code	Yes		(setting s)	(settings)	(settings)	repository /corpname @identifier	(settings)	(settings)	(settings)				
collection	Collection code	Yes		-	-	-	repository /corpname/part	-	lido /descriptiveMetadata /objectRelationWrap /relatedWorksWrap /relatedWorkSet [relatedWorkRelType /term='Kokoelma' or 'kuuluu kokoelmaan' or 'kokoelma'] /relatedWork /displayObject	-				
building	Location, hierarchical (see http://wiki.apache.org/solr/HierarchicalFaceting)	Yes		(setting s)	(settings)	(settings)		(settings)	(settings), administrativeMetadata /rightsWorkWrap /rightsWorkSet /rightsHolder /legalBodyName /appellationValue (up to first slash)	(settings), 852b or 'Ebrary' if 035a contains a code beginning with 'ebr' and containing subsequently only numbers				
Generic Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
language	Language codes in ISO 639-3 format with some collective language codes from ISO 639-2/5	Yes	language	language	language	material- >inLanguage	did->langmaterial- >language@langco de	did- >langmaterial- >language@la ngcode	-	008[35:3], 041ad, 979h				

format	Format codes, hierarchical (see http://wiki.apache.org/solr/HierarchicalFaceting)	Yes		type	type	LearningMaterial	genreform/part	controlaccess->genreform or @level	descriptiveMetadata/objectClassificationWrap/objectWorkTypeWrap/objectWorkType/term	(ks. Marc.php , getFormatFunction, getGamePlatformIds)				
author	Primary authors	No	AllFields, Author	creator	creator	author->person->name tekijät: controlaccessname part, controlaccess->persname->part muut toimijat: relationrelationEntry (relationtype="cpfrelation")	arkistonmuodostaja: origination->namepart, origination->persnamepart tekijät: controlaccessname part, controlaccess->persname->part muut toimijat: relationrelationEntry (relationtype="cpfrelation")	controlaccess->persname	descriptiveMetadata/eventWrap/eventSet/event[eventType/term='valmistus' or 'suunnittelu']/eventActor/actorInRole/actor/nameActorSet/appellationValue	100abcde (by role)				
author_variant	Primary authors variant forms	No	AllFields, Author	-	-	-	origination->namepart, originationpersnamepart, controlaccessname part, controlaccess->persnamepart(@relator='varianttiniimi', 'vaihtoehtoinen nimi', 'vanhentunut nimi')			100a, 700a (by role, initials)				
author_role	Roles of primary authors	No	AllFields, Author	creator	creator	-		controlaccess->persname, controlaccess->corpname	descriptiveMetadata/eventWrap/eventSet/event[eventType/term='valmistus' or 'suunnittelu']/eventActor/actorInRole/actor/nameActorSet/appellationValue	1004e (by role)				
author_facet	Primary authors, secondary authors and corporate authors	Yes		creator, contributor	creator, contributor	author->person->name author->organization->legalName	(author, author_corporate, author2)	controlaccess->persname, controlaccess->corpname	descriptiveMetadata/eventWrap/eventSet/event[eventType/term='valmistus' or 'suunnittelu']/eventActor/actorInRole/actor/nameActorSet/appellationValue	100abc, 110ab, 111ab, 700aqbc, 710ab, 711ab, 979c, 979d				
author_sort	Main author for sorting	No		creator	creator	-		controlaccess->persname, controlaccess->corpname	descriptiveMetadata/eventWrap/eventSet/event[eventType/term='valmistus' or 'suunnittelu']/eventActor/actorInRole/actor/nameActorSet/appellationValue	100abcde (by role)				
author_fuller (DEPRECATED, will be removed)	Fuller forms of primary authors	No	AllFields, Author	-	-	-		-	-	100q				
author-letter (REMOVED, use author_variant)	Main author, name only	Yes		-	-	-		-	-	100a				
AuthorStr (REMOVED, use author_facet)	Main author	Yes		creator	creator	-		controlaccess->persname, controlaccess->corpname (first)	descriptiveMetadata/eventWrap/eventSet/event[eventType/term='valmistus']/eventActor/actorInRole/actor/nameActorSet/appellationValue	100abcde				
author2	Secondary authors	No	AllFields, Author	contributor	contributor	author->person->name	relationsrelation (relationtype="cpfrelation", arcrole='luovuttaja', 'kerääjä', 'vastaanottaja') relationentry	origination->persname	-	100abcde, 700abcde, 900a (by role), 979c, 979d				
author2_variant	Secondary authors variant forms	No	AllFields, Author	-	-	-	-	-	-	100a, 700a (by role, initials)				
author2_role	Secondary authors' roles	No		-	-	-		-	-	1004e, 7004e, 7104e (by role)				
author2_fuller (DEPRECATED, will be removed)	Fuller forms of secondary authors	No		-	-	-		-	-	100q				
author2-role (REMOVED, use author2_role)	Secondary authors' roles	No		-	-	-		-	-	700e, 710e				

author_corporate	Corporate author	No	AllFields, Author	-	-	author->organization->legalName	origination->corpnamepart, controlaccess->corpname->part	controlaccess->corpname, origination->corpname		110ab, 111ab, 710ab, 711ab, 910ab, 911ae				
author_additional	Additional authors	No	AllFields, Author	-	-	-		-		505r				
author_browse	Browsable authors	Yes	AuthorBrowse	creator, contributor	creator, contributor	-		controlaccess->persname, controlaccess->corpname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus' or 'suunnittelu'] /eventActor /actorInRole/actor /nameActorSet /appellationValue	100abcde, 110ab, 111ab, 700abcde, 710ab, 711ab, 979c, 979d				
dedup_id_str_mv	Merge record's ID for deduplicated records					-								
media_type_str_mv	Media types of links found from record metadata.	Yes		-	file attribute type, file extension from link	materialformat, file extension from link	daolinkrole, file extension from link	file extension from link	linkResource attribute formatResource, file extension from link	856q				
title	Record title	No	AllFields, JournalTitle, Title	title	title	title	(Configurable: <i>prependTitleWithSubtitle</i>): (title_short) or (title_sub + title_short)	(Configurable: <i>prependTitleWithSubtitle</i>): (title_short) or (title_sub + title_short)	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue (Preferred langcode is configurable)	245abnp or 240anp				
title_sort	Title for sorting (e.g. leading punctuation characters removed, lowercased)	No		title	title	title	(title)	(title)	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue (Preferred langcode is configurable)	245abnp or 240anp				
title_sub	Subtitle	No		title part after ':'	title part after ':'	title part after ':'	<unittitle localtype=subtitle >alaotsikko</unittitle>	did->unittid	-	245bnp				
title_short	Short title (part before subtitle)	No	AllFields, JournalTitle, Title	title part before ':'	title part before ':'	title part before ':'	did->unittitle + did->unitdate	did->unittitle	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue (Preferred langcode is configurable)	245a or 240anp				
title_full	Full title (e.g. short + sub)	No	AllFields, JournalTitle, Title, TitleBrowse	title	title	title	(title)	(title)	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue (Preferred langcode is configurable)	245 or 240				
title_fullStr	Full title (e.g. short + sub)	Yes		title	title	title		(title)	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue (Preferred langcode is configurable)	245 or 240				
title_alt	Alternative title	No	AllFields, JournalTitle, Title	-	-	title		-	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang=other than 'fi' or @pref='alternate'] (Preferred langcode is configurable)	130adfg klnpst 240adfg hklmnoprs 243adfg hklmnoprs 245ab 246a 505t 730adfg klnpst 740a 940a 979b 979e				

title_old	Old title	No	JournalTitle, Title	-	-	-		-	-	780ast				
title_new	New title	No	AllFields, JournalTitle, Title	-	-	-		-	-	785ast				
physical	Physical description	No		-	-	-		did->physdesc->extent	-	300abcefg, 530abcd				
publisher	Publisher	No	publisher	publisher	publisher	publisher		-	-	260b or 264 [ind 2=1]b				
publisherStr	Publisher	Yes		publisher	publisher	publisher		-	-	260b or 264 [ind 2=1]b				
publishDate	Publication year	Yes	year	date	date	date		-	-	260c or or 264 [ind 2=1]c 008 [7:4]				
edition	Edition	No		-	-	-		-	-	250a				
description	Description (somewhat overlapping with contents)	No	AllFields	-	first value of contents	-	scopecontent->p	scopecontent->p	descriptiveMetadata/objectIdentificationWrap/objectDescriptionWrap/objectDescriptionSet/descriptiveNoteValue	-				
contents	Contents, table of contents	No	AllFields, toc	description	description	description	index->index->indexentry->name->part	-	-	505a, 505t				
url	Record URL	No		identifier starting with http(s) and description starting with http(s)	identifier starting with http(s) and description starting with http(s)	-		-	-	856u				
thumbnail	Thumbnail URL	No		-	-	-		did->daogrp->daoloc["@role="image_thumbnail"]@href	administrativeMetadata/resourceWrap/resourceSet/resourceRepresentation/linkResource	-				
Catalog Specific Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
lccn	Library of Congress Control Number	No		-	-	-		-	-	010a				
ctrlnum	Other control numbers	No		recordID	recordID	recordID		-	-	035a, 036a				
isbn	ISBN in 13 digit version without dashes	No	AllFields, ISN	identifier that looks like an ISBN	identifier that looks like an ISBN, isFormatOf that looks like an ISBN	identifier that looks like an ISBN, isFormatOf that looks like an ISBN		doc->@id	descriptiveMetadata/objectIdentificationWrap/repositoryWrap/resourceSet/workID type="isbn"	020a, 773z				
issn	ISSN as is	No	AllFields, ISN	-	-	-		-	-	022a				
callnumber (DEPRECATED)	Full call number	Yes	CallNumber	-	-	-		-	-	080ab, 084ab, 050ab				
callnumber-a (DEPRECATED)	Main call number	Yes	LccBrowse	-	-	-		-	-	080a, 084a, 050a				
callnumber-first-code (DEPRECATED)	First character of call number	Yes		-	-	-		-	-	first char from 080a, 084a, 050a				
callnumber-first	First call number	Yes								First occurrence of 080ab, 084ab, 050ab				
callnumber-subject	Subject part of call number	Yes								Alphabetic beginning of first occurrence of 090a or 050a				
callnumber-label	Label part of call number	Yes								Up to first period of first occurrence of 090a or 050a				
callnumber-sort	Sortable call number	No								First occurrence of 080ab, 084ab, or sort key created from 050ab				
callnumber-raw	Full call number	No								080ab, 084ab, 050ab				
callnumber-search	Searchable call number	No	CallNumber							080ab, 084ab, 050ab				
dewey-hundreds	Dewey call number, hundreds part	Yes								First occurrence of 082a, 083a				

dewey-tens	Dewey call number, tens part	Yes								First occurrence of 082a, 083a				
dewey-ones	Dewey call number, ones part	Yes								First occurrence of 082a, 083a				
dewey-full	Dewey call number	No								082a, 083a				
dewey-sort	Sortable Dewey call number	No								Sort key from first occurrence of 082a, 083a				
dewey-raw	Full Dewey call number	No								082a, 083a				
dewey-search	Searchable Dewey call number	No	CallNumber							082a, 083a				
dateSpan	Numbering of serials	No		-	-	-		-	-	362a				
series	Series	No	AllFields, JournalTitle, Series, Title	-	relation type="ispartofseries"	-		-	-	440anp, 800abcdfnpqtlv, 830av; if 440/800/830 empty then 490av				
series2	Secondary series	No	AllFields, JournalTitle, Series, Title	-	-	-		-	-					
topic	Subject headings	No	AllFields, Subject, topic	subject	subject	about->thing->name	controlaccess->subjectpart relationsrelation (relationtype="cpfrelation", arrole='aihe', 'forekommer', 'handlar om', 'refereras till') relationentry	controlaccess->subject	descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectConcept /term excluding types 'aihe' and 'iconclass', descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectActor/actor /nameActorSet /appellationValue	567b 600abcdefghijklmnopqrstuvwxyz, 610abcdefghijklmnopqrstuvwxyz, 611acdefghijklmnopqrstuvwxyz, 630adefghklmnopqrstuvwxyz, 650abcdevxyz 653[ind 2=" ", 0, 1, 2, 3]ja				
topic_browse	Subject headings	No	TopicBrowse	subject	subject	about->thing->name		controlaccess->subject	descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectConcept /term excluding types 'aihe' and 'iconclass', descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectActor/actor /nameActorSet /appellationValue	567b 600abcdefghijklmnopqrstuvwxyz, 610abcdefghijklmnopqrstuvwxyz, 611acdefghijklmnopqrstuvwxyz, 630adefghklmnopqrstuvwxyz, 650abcdevxyz (plus 653a for MetaLib records)				
topic_facet	Subject headings	Yes	topic	subject	subject	about->thing->name	controlaccess->subject->part	controlaccess->subject	descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectConcept /term excluding types 'aihe' and 'iconclass', descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectActor/actor /nameActorSet /appellationValue	567b, 600ax, 610ax, 611ax, 630ax, 648x, 650ax, 651x, 655x				
genre	Genre	No	AllFields, Subject, genre	-	-	-		-	-	653[ind 2=6]a, 655abcxyz				
genre_facet	Genre	Yes	genre	-	-	-		-	-	600v, 610v, 611v, 630v, 648v, 650v, 651v, 653[ind 2=6]a, 655a, 655v				

geographic	Geographic subject headings	No	AllFields, Subject, geographic	-	coverage type=" spatial"	-	controlaccessgeogn ame[relator="aihe" or "alueellinen kattavuus" or no relator attribute]->part	controlaccess->geogname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term="käyttö" or 'valmistus'] /eventPlace /displayPlace, descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectPlace /displayPlace, descriptiveMetadata /objectIdentificationW rap/repostoryWrap /repositorySet [type='Current location'] /repositoryLocation /namePlaceSet /appellationValue	370g, 651aevxyz, 653 [ind 2=5]a				
geographic_facet	Geographic subject headings	Yes	geographic	-	coverage type=" spatial"	-	controlaccessgeogn ame[relator="aihe" or "alueellinen kattavuus" or no relator attribute]->part	controlaccess->geogname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term="käyttö" or 'valmistus'] /eventPlace /displayPlace, descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectPlace /displayPlace, descriptiveMetadata /objectIdentificationW rap/repostoryWrap /repositorySet [type='Current location'] /repositoryLocation /namePlaceSet /appellationValue	370g, 600z, 610z, 611z, 630z, 648z, 650z, 651a, 651z, 653[ind 2=5]a, 655z				
era	Chronological subject headings	No	Subject, era	-	coverage type=" temporal"	-	unitdate/	-	objectRelationWrap /subjectWrap /subjectSet/subject /subjectDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventDate /displayDate	388a, 648axxyz, 653 [ind 2=4]a				
era_facet	Chronological subject headings	Yes		-	coverage type=" temporal"	-		-	objectRelationWrap /subjectWrap /subjectSet/subject /subjectDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventDate /displayDate	388a, 630y, 648a, 648y, 650y, 651y, 653[ind 2=4]a, 655y				
illustrated	Whether the work is illustrated	Yes		-	-	-		-	-	leader[6] = 'a' or 't' and (008 [18-21] contains one of 'abcdefghijkmo p' or 006[1-4] contains one of 'abcdefghijkmo p' or 300b contains one of 'illi.', 'illus.', 'kuv.', 'kuvitettu', 'illustrated'				
long_lat	Main coordinates for map search and display on a map (see also location_geo)	Yes		-	-	-		(possible geocoding)	(possible geocoding)	034defg				
For loading correct record driver	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				

recordtype (DEPRECATED)	Deprecated, use record_format. This field is will not be present in newly indexed records.	No												
record_format	Record Type (dc, ead, ead3, lido, marc, qdc, forward, lrmi)	No												
Tracking fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
first_indexed	Date of initial harvest of the record	No												
last_indexed	Date of last update of the record	No												
Hierarchy Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
hierarchytype	Always 'Default'	No		-	-	-	'Default'	'Default'	-	-				
hierarchy_top_id	Top level record ID	No		-	-	-		eadheader->eadid->@identifier or eadheader->eadid + '_' + unitid->@identifier or (ordinal number)	-					
hierarchy_top_title	Top level record title	Yes		-	-	-		eadheader->filedesc->titlemt->titleproper	-					
hierarchy_parent_id	Parent record ID	No		-	-	-		eadheader->eadid->@identifier or eadheader->eadid + '_' + unitid->@identifier or (ordinal number)	-	773w				
hierarchy_parent_title	Parent record title	No		-	relation type="ispartof"	-		Configurable: <i>parentTitleWithUnitId</i> <i>parentTitle</i> (parent unitid) + ' ' + (parent title) or (parent title) lido /descriptiveMetadata /objectRelationWrap /relatedWorksWrap /relatedWorkSet /relatedWorkRelType [term='Kokoelma' or 'kuuluu kokoelmaan' or 'kokoelma' or 'Arkisto' or 'arkisto' or 'Alakokoelma' or 'alakokoelma' or 'Erityiskokoelma' or 'erityiskokoelma' or 'Hankintaerä' or 'hankintaerä'] /relatedWork /displayObject	-	(parent title)				
hierarchy_sequence	Sequence number for sorting the hierarchy	No		-	-	-		(ordinal number)	-					
is_hierarchy_id	Set to same as hierarchy_top_id if the record is a top level record	No		-	-	-		(hierarchy_top_id in a top-level archdesc element)	-	001 for host records				
is_hierarchy_title	Set to same as hierarchy_top_title if the record is a top level record	No		-	-	-		(hierarchy_top_title in a top-level archdesc element)	-	245abnp or 240abnp for host records				
Component Part Fields	Description	Facet Field	Search	DC	QDC		EAD3	EAD	LIDO	MARC				
container_title	Host record title	No	JournalTitle	-	-	-		-	-	773t				
container_volume	Host record volume	No		-	-	-		-	-	773g				
container_issue	Host record issue	No		-	-	-		-	-	773g				
container_start_page	Start page in the host record	No		-	-	-		-	-	773g				
container_reference	Complete reference to host record	No		-	-	-		-	-	773g				
Museum /EAD Material Fields	Description	Facet Field	Search	DC	QDC		EAD3	EAD	LIDO	MARC				
measurements	Measurements	No		-	-	-		did->dimensions	descriptiveMetadata /objectIdentificationWrap /objectMeasurementsWrap /objectMeasurementsSet /displayObjectMeasurements	-				

material	Material	Yes		-	-	-	did->physdesc + did/physdesc@label	did->physdesc	descriptiveMetadata/eventWrap/eventSet/term=valmistus/eventMaterialsTech/materialsTech/termMaterialsTech/term or descriptiveMetadata/eventWrap/eventSet/event[eventType/term=valmistus]eventMaterialsTech/displayMaterialsTech	-				
identifier	Identifier	Yes		-	-	-	did->unitid	did->unitid	descriptiveMetadata/objectIdentificationWrap/repositoryWrap/repositorySet/workID	-				
culture	Culture	Yes		-	-	-		-	descriptiveMetadata/eventWrap/eventSet/event/culture/term	-				
rights	Rights (holder)	Yes		-	-	-			administrativeMetadata/resourceWrap/resourceSet/rightsResource/rightsHolder/legalBodyName/appellationValue	-				
Educational Fields	Description	Facet Field				LRMI								
educational_audience_str_mv	Educational Role	Yes				educationalAudience->educationalRole								
educational_level_str_mv	Educational Level	Yes				alignmentObject->alignmentType='educationalLevel'								
educational_aim_str_mv	Objective and Content	Yes				alignmentObject->alignmentType='teaches'								
educational_subject_str_mv	Educational Subject	Yes				alignmentObject->alignmentType='educationalSubject'								
educational_material_type_str_mv	Learning Resource Type	Yes				type								
Finna Custom Dynamic Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
online_boolean	True for records available online	Yes			http/ftp url in doc->relation	True if doc->material	True if did->daoset->dao[href] exists	True if did->daogrp->daoloc[href] exists	True if lido->administrativeMetadata->resourceWrapsresourceSet->resourceRepresentation->linkResource exists	True if any: 856u contains an http/ftp URL and ind2 is '0' or '1' and subfield 3 does not exist 338b = 'cr'				
online_str_mv	Contains source ID(s) for records available online	No				True if doc->material								
free_online_boolean	True for records freely available online	Yes				True if doc->material								
free_online_str_mv	Contains source ID(s) for records freely available online	No				True if doc->material								
free_online_boolean	True for records freely available online	Yes				True if doc->material								
free_online_str_mv	Contains source ID(s) for records freely available online	No				True if doc->material								
main_date_str	Record main year (e.g. publication or manufacturing year)	Yes		date	date	date	didunitdate esim: <unitdate normal="1977-07-01/1989-10-31">01.07.1977-31.10.1989</unitdate>	did->unitdate	descriptiveMetadata/eventWrap/eventSet/event[eventType/term=valmistus]/eventDate/displayDate or descriptiveMetadata/eventWrap/eventSet/event[eventType/term=valmistus]/periodName/term	260c or 008[7:4]				

location_g eo	Main coordinates for map search and display on a map, multiple values supported	No		-	-	-	controlaccess /geogname /geographiccoordinates [coordinatesystem="WGS84"]	geogname / geographiccoordinates (+ @coordinate system) (possible geocoding)	descriptiveMetadata /eventWrap/eventSet /event/eventPlace /place/gml descriptiveMetadata /objectIdentificationWrap/repositoryWrap/repositorySet/repositoryLocation/gml (possible geocoding)	034defg				
unit_datera nge	Main date range (e.g. manufacturing date interval)	No		-	-	-	did->unitdate	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term="valmistus"] /eventDate /displayDate or lido /descriptiveMetadata /eventWrap/eventSet /event[eventType /term="valmistus"] /periodName/term	-				
artist_str_ mv	Artist name	Yes		-	-	-		-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term="valmistus"] /eventActor /actorInRole[roleActor /term="taiteilija"]/actor /nameActorSet /appellationValue	-				
photograp her_str_mv	Photographer name	Yes		-	-	-		-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term="valmistus"] /eventActor /actorInRole[roleActor /term="valokuvaaja"] /actor/nameActorSet /appellationValue	-				
finder_str_ mv	Finder name	Yes		-	-	-		-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term="löytöminen"] /eventActor /actorInRole[roleActor /term="löytäjä"]/actor /nameActorSet /appellationValue	-				
manufactur er_str_mv	Manufacturer name	Yes		-	-	-		-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term="valmistus"] /eventActor /actorInRole[roleActor /term="valmistaja"] /actor/nameActorSet /appellationValue	-				
designer_s tr_mv	Designer name	Yes		-	-	-		-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term="suunnittelu"] /eventActor /actorInRole[roleActor /term="suunnittelija"] /actor/nameActorSet /appellationValue	-				
classificati on_txt_mv	Classification	Yes	Classification	-	-	-		-	lido /descriptiveMetadata /objectClassificationWrap /classificationWrap /classification/term	050ab, 060ab, 080abx, 084				
exhibition_ str_mv	Exhibition name	Yes		-	-	-		-	lido /descriptiveMetadata /eventWrap/eventSet /event[eventType /term="näyttely"] /eventName /appellationValue	-				
creation_d aterange	Creation date range	No		-	-	-		-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term="valmistus"] /eventDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term="valmistus"] /periodName/term	-				
search_dat erange_mv	Search date range	No					unitdate							

use_datara nge	Date range of use	No		-	-	-		-	descriptiveMetadata /eventWrap/eventSet /term=käyttö] /eventDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term=käyttö] /periodName/term	-				
finding_dat erange	Date range of finding	No		-	-	-		-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term=löytöminen] /eventDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term=löytöminen] /periodName/term	-				
source_str _mv	Institution or data source id from settings	Yes		-	-	-		-	-	-				
datasource _str_mv	Data source id from settings	Yes		-	-	-		-	-	-				
merged_b oolean	True for merged records representing multiple records	No		-	-	-		-	-	-				
merged_ch ild_boolean	True for original records merged to a merged record	No		-	-	-		-	-	-				
hidden_co mponent_b oolean	True for component parts merged into their host records	No		-	-	-		-	-	-				
other_issn _isn_mv	Related ISSN numbers	No		-	-	-		-	-	440x, 490x, 730x, 773x, 776x, 780x, 785x, 830x				
other_issn _str_mv (D EPRECAT ED, use other_iss n_isn_mv)	Related ISSN numbers	No	ISN	-	-	-		-	-	440x, 490x, 730x, 773x, 776x, 780x, 785x, 830x				
linking_iss n_str_mv	Linking ISSN (ISSN-L)	No		-	-	-		-	-	022l				
holdings_t xtP_mv	Holdings location	No	Shelf Location	-	-	-		-	-	852abhz + data source id, 952bcoh + data source id (Koha)				
online_urls _str_mv	Online URLs	No			relation, file (kk extension)	material (url, name)				url=856u, text=856y or 856z				
subtitle_In g_str_mv	Subtitle language codes in ISO 639-3 format with some collective language codes from ISO-639-2 /5	Yes		-	-	-		-	-	041j				
original_In g_str_mv	Language of original work in ISO 639-3 format with some collective language codes from ISO 639-2 /5	Yes		-	-	-		-	-	041[ind 1=0]a, 041h				
publication _place_txt _mv	Place of publication	No	AllFields	-	-	-		-	-	260a, 264[ind 2=1]a				
project_id_ str_mv	Project ID	No		-	-	-		-	-	960a (Arto, Fennica, Helka)				
ismn_isn_ mv	ISMN	No	AllFields	-	-	-		-	-	024[ind 1=2]a				
isrc_isn_mv	ISRC	No	AllFields	-	-	-		-	-	024[ind 1=0]a				
ean_isn_mv	EAN	No	AllFields	-	-	-		-	-	024[ind 1=3]a				
nbn_isn_mv	NBN	No	AllFields	-	-	-		-	-	015a				
upc_isn_mv	UPC	No	AllFields	-	-	-		-	-	024[ind 1=1]a				
category_s tr_mv	Category (hierarchical)	Yes		-	-	-		-	-	650ax (when enabled for the data source, SFX records only), 886[2=local, a=kategoria or a=kategorii]c/d, HILCC (when enabled for the data source)				
title_txtP	Title (unstemmed)	No	Title, AllFields	(copy of title field)	(copy of title field)	(copy of title field)		(copy of title field)	(copy of title field)	(copy of title field)				

main_date	TrieDateField version of record's main date. Can be used for e.g. date-based boosting. Make sure not to use bare "NOW" in the query (result can't be cached). Use "NOW /DAY" instead.	No		date	date	date	did->unitdate	did->unitdate	descriptiveMetadata /eventWrap/eventSet /term=valmistus] /eventDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term=valmistus] /periodName/term	260c or 008[7:4]				
collection_txt_mv	Collection in searchable form	No	AllFields	(copy of collection field)	(copy of collection field)	(copy of collection field)		(copy of collection field)	(copy of collection field)	(copy of collection field)				
usage_rights_str_mv	Usage rights code. The following codes are available: usage_A = "Free use" usage_B = "Derivatives, also commercial" usage_C = "No derivatives, also commercial" usage_D = "Derivatives, non-commercial" usage_E = "No derivatives, non-commercial" usage_F = "Permission required / unknown"	Yes			rights	rights	<control> <rightsdeclaration> <abbr>CC0</abbr> <citation href="https://creativecommons.org/publicdomain/zero/1.0/">CC0 1.0 Universal (CC0 1.0)</citation>	userrestrict->p (accessrestrict->p)	administrativeMetadata/resourceWrap /resourceSet /rightsResource /rightsType /conceptID	Value based on 540c when subfield 3 is not 'metadata'				
major_genre_str_mv	Major Genre. The following codes are available: fiction nonfiction music	Yes								Value based on YKL (084 where \$2=ykl) or UDK (080) classification				
building_sub_str_mv	Sublocation (e.g. department)	Yes								One of the following values based on 852c if configured: 1 = "Adults" 2 = "Children and Youth" 3 = "Music" 4 = "Magazines" 5 = "Local collection" 6 = "Stacks" 7 = "Other"				
original_id_str_mv	Original record ID	No								035a when resource type from 886 is 'tietokanta' or 'data bas'				
warnings_str_mv	Metadata content processing issues	No						May be one of following (at least): * invalid end date * invalid date range	May be one of following (at least): * invalid date * invalid date range * gml polygon missing outer boundary * gml linestring missing coordinates * empty gml pos in point * empty gml coordinates in point * gml point missing data * invalid gml coordinates * invalid end date	May be one of following (at least): * invalid date range in 008 * invalid coordinates in 034 * invalid field tag 'ddd' * indicator 1 missing * indicator 2 missing * missing subfields * missing subfields in ddd * invalid subfields * invalid subfields in ddd				

[illegible]

geographic _id_str_mv	Geographic place identifiers (may include URIs and other identifiers)	No					controlaccessgeogn ame[relator="aihe" or "alueellinen kattavuus" or no relator attribute] /@identifier		descriptiveMetadata /eventWrap/eventSet /event[eventType /term="valmistus"] /eventPlace/place /placeID, descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectPlace/place /placeID, descriptiveMetadata /objectIdentificationW rap/repositoryWrap /repositorySet /repositoryLocation /placeID[type="prt" or 'kiinteistötunnus' or 'URI']					
--------------------------	--	----	--	--	--	--	---	--	--	--	--	--	--	--