

Kenttien mappaukset eri formaateista Finnan indeksiin

Mappings of fields from different record formats to Finna's main index

Main Index - Pääindeksi

See also the [authority index page](#).

Core Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3 (new organisations)	EAD2002 (old version)	LIDO	MARC				
id	Unique identifier	No	id, ids	recordID	recordID	recordID		eadheader->eadid->@identifier or eadheader->eadid + '-' + unitid->@identifier or (ordinal number) Huom: mikäli käytetään 2-tasoista hierarkiaa (1. arkisto / arkistokokoelma, 2. arkistoyksikkö) eadheader ja archdesc - elementtien id:t tulee olla samat: ead->eadheader->eadid == ead->archdesc->unitid	lidoRecID	001				
fullrecord	Original record data	No		record XML	record XML	record XML		record XML	record XML	record ISO2709 or XML				
allfields	All searchable information that doesn't fit into other searchable fields.	No	AllFields	(all fields)	(all fields)	all fields except 'format', 'id', 'identifier', 'date', 'dateCreate', 'dateModified', 'filesize', 'inLanguage', 'position', 'recordID', 'rights', 'targetUrl', 'url'		(all fields)	SOLR fields: title, description, format, author, topic, material, measurements, identifier, culture	Fields 020, 024, 025, 026, 027, 028, 100 - 840, 856, 880, 900, 910, 911, 940, 952 and 979 except 300, 336 and 337 and subfields 6502, 856q and 979a				
fulltext	Full text	No	AllFields	-	-	-		-	-	-				
Institutional Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
institution	Institution code	Yes		(settings)	(settings)	(settings)	repository/corpname @identifier	(settings)	(settings)	(settings)				
collection	Collection code	Yes		-	-	-	repository/corpname/part	-	lido /descriptiveMetadata /objectRelationWrap /relatedWorksWrap /relatedWorkSet [relatedWorkRelType /term='Kokoelma' or 'kuuluu kokoelmaan' or 'kokoelma'] /relatedWork /displayObject	-				
building	Location, hierarchical (see http://wiki.apache.org/solr/HierarchicalFaceting)	Yes		(settings)	(settings)	(settings)		(settings)	(settings), administrativeMetadata/rightsWorkWrap /rightsWorkSet /rightsHolder /legalBodyName /appellationValue (up to first slash)	(settings), 852b or 'Ebrary' if 035a contains a code beginning with 'ebr' and containing subsequently only numbers				
Generic Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
language	Language codes in ISO 639-3 format with some collective language codes from ISO 639-2/5	Yes	language	language	language	material->inLanguage	did->langmaterial->language@langcode	did->langmaterial->language@langcode	-	008[35:3], 041ad, 979h				

format	Format codes, hierarchical (see http://wiki.apache.org/solr/HierarchicalFaceting)	Yes		type	type	LearningMaterial	genreform/part	controlaccess->genreform or @level	descriptiveMetadata /objectClassification Wrap /objectWorkTypeWrap /objectWorkType /term	(ks. Marc.php , getFormatFunc ja getGamePlat formids)					
author	Primary authors	No	AllFields, Author	creator	creator	author->person->name	arkistonmuodostaja: origination->namepart, origination->persnamepart tekijät: controlaccessname part, controlaccess->persname->part muut toimijat: relationrelationEntry (relationtype="cpfrrelation")	controlaccess->persname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus' or 'suunnittelu'] /eventActor /actorInRole/actor /nameActorSet /appellationValue	100abcde (by role)					
author_variant	Primary authors variant forms	No	AllFields, Author	-	-	-	origination->namepart, originationpersnam epart, controlaccessname part, controlaccess->persnamepart(@re lator=variantinimi', 'vaihtoehtoinen nimi', 'vanhentunut nimi')			100a, 700a (by role, initials)					
author_role	Roles of primary authors	No	AllFields, Author	creator	creator	-		controlaccess->persname, controlaccess->corpname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus' or 'suunnittelu'] /eventActor /actorInRole/actor /nameActorSet /appellationValue	1004e (by role)					
author_facet	Primary authors, secondary authors and corporate authors	Yes		creator, contribu tor	creator, contribut or	author->person->name author->organizatio n->legalName	(author, author_corporate, author2)	controlaccess->persname, controlaccess->corpname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus' or 'suunnittelu'] /eventActor /actorInRole/actor /nameActorSet /appellationValue	100abc, 110ab, 111ab, 700aabc, 710ab, 711ab, 979c, 979d					
author_sort	Main author for sorting	No		creator	creator	-		controlaccess->persname, controlaccess->corpname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus' or 'suunnittelu'] /eventActor /actorInRole/actor /nameActorSet /appellationValue	100abcde (by role)					
author_fuller (DEPREC ATED, will be removed)	Fuller forms of primary authors	No	AllFields, Author	-	-	-		-	-	100q					
author-letter (RE MOVED, use author_variant)	Main author, name only	Yes		-	-	-		-	-	100a					
AuthorStr (REMOVED , use author_fac et)	Main author	Yes		creator	creator	-		controlaccess->persname, controlaccess->corpname (first)	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventActor /actorInRole/actor /nameActorSet /appellationValue	100abcde					
author2	Secondary authors	No	AllFields, Author	contribu tor	contribut or	author->person->name	relationsrelation (relationtype="cpfrrelation", arcrole='luovuttaja', 'kerääjä', 'vastaanottaja') relationentry	origination->persname	-	100abcde, 700abcde, 900a (by role), 979c, 979d					
author2_variant	Secondary authors variant forms	No	AllFields, Author	-	-	-	-	-	-	100a, 700a (by role, initials)					
author2_rol e	Secondary authors' roles	No		-	-	-		-	-	1004e, 7004e, 7104e (by role)					
author2_ful ler (DEPREC ATED, will be removed)	Fuller forms of secondary authors	No		-	-	-		-	-	100q					
author2-rol e (REMOVED, use author2_rol e)	Secondary authors' roles	No		-	-	-		-	-	700e, 710e					

author_corporate	Corporate author	No	AllFields, Author	-	-	author->organization->legalName	origination->corpnamepart, controlaccess->corname->part	controlaccess->corname, origination->corname		110ab, 111ab, 710ab, 711ab, 910ab, 911ae				
author_additional	Additional authors	No	AllFields, Author	-	-	-			-	505r				
author_browse	Browsable authors	Yes	AuthorBrowse	creator, contributor	creator, contributor	-			controlaccess->persname, controlaccess->corname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus' or 'suunnittelu'] /eventActor /actorInRole/actor /nameActorSet /appellationValue	100abcde, 110ab, 111ab, 700abcde, 710ab, 711ab, 979c, 979d			
dedup_id_str_mv	Merge record's ID for deduplicated records					-								
media_type_str_mv	Media types of links found from record metadata.	Yes		-	file attribute type, file extension from link	materialform at, file extension from link	daolinkrole, file extension from link	file extension from link	linkResource attribute formatResource, file extension from link	856q				
title	Record title	No	AllFields, JournalTitle, Title	title	title	(Configurable: prep endTitleWithSubTitle):	(Configurable: prependTitleWithSubTitle):	(title_short) or (title_sub + title_short)	(title_sub + title_short)	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue	245abnp or 240anp			
title_sort	Title for sorting (e.g. leading punctuation characters removed, lowercased)	No		title	title	title	(title)	(title)	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue	245abnp or 240anp				
title_sub	Subtitle	No		title part after ':'	title part after ':'	title part after ':'	<unititle locality=subtitle>alaotsikko </unititle>	did->unitid	-	245bnp				
title_short	Short title (part before subtitle)	No	AllFields, JournalTitle, Title	title part before ':'	title part before ':'	title part before ':'	did->unititle + did->unitdate	did->unititle	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue	245a or 240anp				
title_full	Full title (e.g. short + sub)	No	AllFields, JournalTitle, Title, TitleBrowse	title	title	title	(title)	(title)	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue	245 or 240				
title_fullStr	Full title (e.g. short + sub)	Yes		title	title	title		(title)	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='fi'] or descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue	245 or 240				
title_alt	Alternative title	No	AllFields, JournalTitle, Title	-	-	title		-	descriptiveMetadata /objectIdentificationWrap/titleWrap/titleSet /appellationValue [@lang='en']	<ul style="list-style-type: none"> • 130adfg klnpst • 240adfg hklmnp rs • 243adfg hklmnp rs • 245ab • 246a • 505t • 730adfg klnpst • 740a • 940a • 979b • 979e 				
title_old	Old title	No	JournalTitle, Title	-	-	-		-	-	780ast				
title_new	New title	No	AllFields, JournalTitle, Title	-	-	-		-	-	785ast				
physical	Physical description	No		-	-	-		did->physdesc->extent	-	300abcefg, 530abcd				
publisher	Publisher	No	publisher	publisher	publisher	publisher			-	-	260b or 264 [ind 2=1]b			
publisherStr	Publisher	Yes		publisher	publisher	publisher			-	-	260b or 264 [ind 2=1]b			

publishDate	Publication year	Yes	year	date	date	date		-	-	260c or or 264 [ind 2=1]c 008 [7:4]			
edition	Edition	No		-	-	-		-	-	250a			
description	Description (somewhat overlapping with contents)	No	AllFields	-	first value of contents	-	scopecontent->p	scopecontent->p	descriptiveMetadata /objectIdentificationWrap /objectDescriptionWrap /objectDescriptionSet /descriptiveNoteValue	-			
contents	Contents, table of contents	No	AllFields, toc	descriptor	description	description	index->index->indexentry->name->part	-	-	505a, 505t			
url	Record URL	No		identifier starting with http(s) and description starting with http(s)	identifier starting with http(s) and description starting with http(s)	-		-	-	856u			
thumbnail	Thumbnail URL	No		-	-	-		did->daogr->daolc [@role="image_thumbnail"]@href	administrativeMetadata /resourceWrap /resourceSet /resourceRepresentation/linkResource	-			
Catalog Specific Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC			
lccn	Library of Congress Control Number	No		-	-	-		-	-	010a			
ctrlnum	Other control numbers	No		recordID	recordID	recordID		-	-	035a, 036a			
isbn	ISBN in 13 digit version without dashes	No	AllFields, ISBN	identifier that looks like an ISBN	identifier that looks like an ISBN, isFormatOf that looks like an ISBN	identifier that looks like an ISBN, isFormatOf that looks like an ISBN		doc->@id	descriptiveMetadata /objectIdentificationWrap/repositoryWrap /repositorySet/workID type="isbn"	020a, 773z			
issn	ISSN as is	No	AllFields, ISBN	-	-	-		-	-	022a			
callnumber (DEPRECATED)	Full call number	Yes	CallNumber	-	-	-		-	-	080ab, 084ab, 050ab			
callnumber -a (DEPRECATED)	Main call number	Yes	LccBrowse	-	-	-		-	-	080a, 084a, 050a			
callnumber -first-code (DEPRECATED)	First character of call number	Yes		-	-	-		-	-	first char from 080a, 084a, 050a			
callnumber -first	First call number	Yes								First occurrence of 080ab, 084ab, 050ab			
callnumber -subject	Subject part of call number	Yes								Alphabetic beginning of first occurrence of 090a or 050a			
callnumber -label	Label part of call number	Yes								Up to first period of first occurrence of 090a or 050a			
callnumber -sort	Sortable call number	No								First occurrence of 080ab, 084ab, or sort key created from 050ab			
callnumber -raw	Full call number	No								080ab, 084ab, 050ab			
callnumber -search	Searchable call number	No	CallNumber							080ab, 084ab, 050ab			
dewey-hundreds	Dewey call number, hundreds part	Yes								First occurrence of 082a, 083a			
dewey-tens	Dewey call number, tens part	Yes								First occurrence of 082a, 083a			
dewey-ones	Dewey call number, ones part	Yes								First occurrence of 082a, 083a			
dewey-full	Dewey call number	No								082a, 083a			
dewey-sort	Sortable Dewey call number	No								Sort key from first occurrence of 082a, 083a			

dewey-raw	Full Dewey call number	No								082a, 083a					
dewey-search	Searchable Dewey call number	No	CallNumber							082a, 083a					
dateSpan	Numbering of serials	No	-	-	-	-	-	-	-	362a					
series	Series	No	AllFields, JournalTitle, Series, Title	-	relation type="ispartofseries"	-				440anp, 800abcdfpqtlv , 830av; if 440 /800/830 empty then 490av					
series2	Secondary series	No	AllFields, JournalTitle, Series, Title	-	-	-									
topic	Subject headings	No	AllFields, Subject, topic	subject	subject	about->thing->name	controlaccess->subjectpart relationsrelation (relationtype="cpfrelation", arcrole='aihe', 'forekommer', 'handlar om', 'refereras till') relationshipentry	controlaccess->subject	descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectConcept /term excluding types 'aihe' and 'iconclass', descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectActor/actor /nameActorSet /appellationValue	567b 600abcdefghijklmnopqrstuvwxyz, 610abcdefghijklmnopqrstuvwxyz, 611abcdefghijklmnopqrstuvwxyz, 630abcdefghijklmnopqrstuvwxyz, 650abcdefghijklmnopqrstuvwxyz 653[ind 2=1 , 0, 1, 2, 3]]a					
topic_browse	Subject headings	No	TopicBrowse	subject	subject	about->thing->name		controlaccess->subject	descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectConcept /term excluding types 'aihe' and 'iconclass', descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectActor/actor /nameActorSet /appellationValue	567b 600abcdefghijklmnopqrstuvwxyz, 610abcdefghijklmnopqrstuvwxyz, 611abcdefghijklmnopqrstuvwxyz, 630abcdefghijklmnopqrstuvwxyz, 650abcdefghijklmnopqrstuvwxyz (plus 653a for MetaLib records)					
topic_facet	Subject headings	Yes	topic	subject	subject	about->thing->name	controlaccess->subject->part	controlaccess->subject	descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectConcept /term excluding types 'aihe' and 'iconclass', descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectActor/actor /nameActorSet /appellationValue	567b, 600ax, 610ax, 611ax, 630ax, 648x, 650ax, 651x, 655x					
genre	Genre	No	AllFields, Subject, genre	-	-	-				653[ind 2=6]a, 655abcxyz					
genre_facet	Genre	Yes	genre	-	-	-				600v, 610v, 611v, 630v, 648v, 650v, 651v, 653[ind 2=6]a, 655a, 655v					
geographic	Geographic subject headings	No	AllFields, Subject, geographic	-	coverage type="spatial"	-	controlaccessgeogn ame[relator="aihe" or "alueellinen kattavuus" or no relator attribute]->part	controlaccess->geogname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='käyttö' or 'valmistus'] /evenPlace /displayPlace, descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectPlace /displayPlace, descriptiveMetadata /objectIdentificationW rap/repositoryWrap /repositorySet [type='Current location'] /repositoryLocation /namePlaceSet /appellationValue	370g, 651aevxyz, 653 [ind 2=5]a					

geographic_facet	Geographic subject headings	Yes	geographic	-	coverage type="spatial"	-	controlaccessgeogname[relator="aihe" or "alueellinen kattavuus" or no relator attribute]->part	controlaccess->geogname	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='käyttö' or 'valmistus'] /eventPlace /displayPlace, descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectPlace /displayPlace, descriptiveMetadata /objectIdentificationWrap /repositoryWrap /repositorySet [type='Current location'] /repositoryLocation /namePlaceSet /appellationValue	370g, 600z, 610z, 611z, 630z, 648z, 650z, 651a, 651z, 653[ind 2=5]a, 655z				
era	Chronological subject headings	No	Subject, era	-	coverage type="temporal"	-	unitdate/	-	objectRelationWrap /subjectWrap /subjectSet/subject /subjectDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventDate /displayDate	388a, 648avxyz, 653 [ind 2=4]a				
era_facet	Chronological subject headings	Yes		-	coverage type="temporal"	-		-	objectRelationWrap /subjectWrap /subjectSet/subject /subjectDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventDate /displayDate	388a, 630y, 648a, 648y, 650y, 651y, 653[ind 2=4]a, 655y				
illustrated	Whether the work is illustrated	Yes		-	-	-		-	leader[6] = 'a' or 't' and (008 [18-21] contains one of 'abcdefghijklmop' or 006[1-4] contains one of 'abcdefghijklmop' or 300b contains one of 'ill.', 'illus.', 'kuv.', 'kuvittetu', 'illustrated'					
long_lat	Main coordinates for map search and display on a map (see also location_geo)	Yes		-	-	-		(possible geocoding)	(possible geocoding)	034defg				
For loading correct record driver	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
recordtype (DEPRECATED)	Deprecated, use record_format. This field is will not be present in newly indexed records.	No												
record_format	Record Type (dc, ead, ead3, lido, marc, qdc, forward, lrmi)	No												
Tracking fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
first_indexed	Date of initial harvest of the record	No												
last_indexed	Date of last update of the record	No												
Hierarchy Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
hierarchyype	Always 'Default'	No		-	-	-	'Default'	'Default'	-	-				

hierarchy_top_id	Top level record ID	No		-	-	-		eadheader->eadid->@identifier or eadheader->eadid + ' ' + unitid->@identifier or (ordinal number)	-					
hierarchy_top_title	Top level record title	Yes		-	-	-		eadheader->filedesc->titlestmt->titleproper	-					
hierarchy_parent_id	Parent record ID	No		-	-	-		eadheader->eadid->@identifier or eadheader->eadid + ' ' + unitid->@identifier or (ordinal number)	-	773w				
hierarchy_parent_title	Parent record title	No		-	relation type="ispartof"	-		Configurable: p rependParentTitleWithUnitId (parent unitid) + ' ' + (parent title) or (parent title)	lido /descriptiveMetadata /objectRelationWrap /relatedWorksWrap /relatedWorkSet [relatedWorkRelType /term='Kokoelma' or 'kuuluu kokoelmaan' or 'kokoelma' or 'Arkisto' or 'arkisto' or 'Alakokoelma' or 'alakokoelma' or 'Erityskokoelma' or 'erityiskokoelma' or 'Hankintaera' or 'hankintaera'] /relatedWork /displayObject	(parent title)				
hierarchy_sequence	Sequence number for sorting the hierarchy	No		-	-	-		(ordinal number)	-					
is_hierarchy_id	Set to same as hierarchy_top_id if the record is a top level record	No		-	-	-		(hierarchy_top_id in a top-level archdesc element)	-	001 for host records				
is_hierarchy_title	Set to same as hierarchy_top_title if the record is a top level record	No		-	-	-		(hierarchy_top_title in a top-level archdesc element)	-	245abnp or 240abnp for host records				
Component Part Fields	Description	Facet Field	Search	DC	QDC		EAD3	EAD	LIDO	MARC				
container_title	Host record title	No	JournalTitle	-	-	-		-	-	773t				
container_volume	Host record volume	No		-	-	-		-	-	773g				
container_issue	Host record issue	No		-	-	-		-	-	773g				
container_start_page	Start page in the host record	No		-	-	-		-	-	773g				
container_reference	Complete reference to host record	No		-	-	-		-	-	773g				
Museum/EAD Material Fields	Description	Facet Field	Search	DC	QDC		EAD3	EAD	LIDO	MARC				
measurements	Measurements	No		-	-	-		did->dimensions	descriptiveMetadata /objectIdIdentificationWrap /objectMeasurementsWrap /objectMeasurementsSet /displayObjectMeasurements	-				
material	Material	Yes		-	-	-	did->physdesc + did /physdesc@label	did->physdesc	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmisteus'] eventMaterialsTech /materialsTech /termMaterialsTech /term or descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmisteus'] eventMaterialsTech /displayMaterialsTech	-				
identifier	Identifier	Yes		-	-	-	did->unitid	did->unitid	descriptiveMetadata /objectIdIdentificationWrap/repositoryWrap /repositorySet/workID	-				
culture	Culture	Yes		-	-	-		-	descriptiveMetadata /eventWrap/eventSet /event[culture/term]	-				

rights	Rights (holder)	Yes		-	-			administrativeMetadata/resourceWrap/resourceSet/rightsResource/rightsHolder/legalBodyName/appellationValue	-					
Education al Fields	Description	Facet Field				LRMI								
educationa l_audience _str_mv	Educational Role	Yes				educational Audience->e ducationalRole								
educationa l_level_str _mv	Educational Level	Yes				alignmentOb ject->align mentType='educational Level'								
educationa l_aim_str _mv	Objective and Content	Yes				alignmentOb ject->align mentType='t eaches'								
educationa l_subject_s tr_mv	Educational Subject	Yes				alignmentOb ject->align mentType='educational Subject'								
educationa l_material_type_str_mv	Learning Resource Type	Yes				type								
Finna Custom Dynamic Fields	Description	Facet Field	Search	DC	QDC	LRMI	EAD3	EAD	LIDO	MARC				
online_boo lean	True for records available online	Yes			http/ftp url in doc->relation	True if doc->material	True if did->daoset->daogr->daol oc[href] exists	True if did->daoset->daogr->daol oc[href] exists	True if lido->administrativeMetad ata->resourceWrap/resourceSet->resourceRepresentation->linkResource exists	True if any:	<ul style="list-style-type: none"> • 856u contains an http /ftp URL and ind2 is '0' or '1' and subfield 3 does not exist • 338b = 'cr' 			
online_str_mv	Contains source ID(s) for records available online	No				True if doc->material								
free_online _boolean	True for records freely available online	Yes				True if doc->material								
free_online _str_mv	Contains source ID(s) for records freely available online	No				True if doc->material								
free_online _boolean	True for records freely available online	Yes				True if doc->material								
free_online _str_mv	Contains source ID(s) for records freely available online	No				True if doc->material								
main_date _str	Record main year (e.g. publication or manufacturing year)	Yes		date	date	date	didunitdate esim: <unitdate normal="1977-07-01/1989-10-31">01.07.1977-31.10.1989</unitdate>	did->unitdate	descriptiveMetadata /eventWrap/eventSet /event[eventType /term=valmistas]	260c or 008[7:4]				
location_g eo	Main coordinates for map search and display on a map, multiple values supported	No		-	-	-	controlaccess /geoname /geographiccoordinates [coordinatesystem="WGS84"]	geoname / ge ographiccoordin ates (+@coordinate system) (possible geocoding)	descriptiveMetadata /eventWrap/eventSet /event[eventPlace /place/gml]	034defg				
unit_datera nge	Main date range (e.g. manufacturing date interval)	No		-	-	-	did->unitdate	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term=valmistas]	-				

artist_str_mv	Artist name	Yes		-	-	-	-	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventActor /actorInRole[roleActor /term='taiteilija']/actor /nameActorSet /appellationValue	-						
photographer_str_mv	Photographer name	Yes		-	-	-	-	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventActor /actorInRole[roleActor /term='valokuvaaja'] /actor/nameActorSet /appellationValue	-						
finder_str_mv	Finder name	Yes		-	-	-	-	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='löytyminen'] /eventActor /actorInRole[roleActor /term='löytäjä']/actor /nameActorSet /appellationValue	-						
manufacturer_str_mv	Manufacturer name	Yes		-	-	-	-	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventActor /actorInRole[roleActor /term='valmistaja'] /actor/nameActorSet /appellationValue	-						
designer_st_mv	Designer name	Yes		-	-	-	-	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='suunnittelu'] /eventActor /actorInRole[roleActor /term='suunnittelija'] /actor/nameActorSet /appellationValue	-						
classification_txt_mv	Classification	Yes	Classification	-	-	-	-	-	lido /descriptiveMetadata /objectClassification Wrap /classificationWrap /classification/term	050ab, 060ab, 080abx, 084						
exhibition_str_mv	Exhibition name	Yes		-	-	-	-	-	lido /descriptiveMetadata /eventWrap/eventSet /event[eventType /term='näyttely'] /eventName /appellationValue	-						
creation_daterange	Creation date range	No		-	-	-	-	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /periodName/term	-						
search_daterange_mv	Search date range	No					unitdate									
use_daterange	Date range of use	No		-	-	-	-	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='käyttö'] /eventDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term='käyttö'] /periodName/term	-						
finding_daterange	Date range of finding	No		-	-	-	-	-	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='löytyminen'] /eventDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term='löytyminen'] /periodName/term	-						
source_str_mv	Institution or data source id from settings	Yes		-	-	-	-	-		-	-					
datasource_str_mv	Data source id from settings	Yes		-	-	-	-	-		-	-					
merged_boolean	True for merged records representing multiple records	No		-	-	-	-	-		-	-					
merged_child_boolean	True for original records merged to a merged record	No		-	-	-	-	-		-	-					

hidden_component_boolean	True for component parts merged into their host records	No		-	-	-		-	-	-				
other_isnn_isn_mv	Related ISSN numbers	No		-	-	-		-	-	440x, 490x, 730x, 773x, 776x, 780x, 785x, 830x				
other_isnn_str_mv (D_EPRECAT_ED, use other_isn_isn_mv)	Related ISSN numbers	No	ISN	-	-	-		-	-	440x, 490x, 730x, 773x, 776x, 780x, 785x, 830x				
linking_isn_str_mv	Linking ISSN (ISSN-L)	No		-	-	-		-	-	022l				
holdings_t_xtp_mv	Holdings location	No	Shelf Location	-	-	-		-	-	852abhz + data source id, 952bc0h + data source id (Koha)				
online_urls_str_mv	Online URLs	No			relation_file (kk extension)	material(url, name)				url=856u, text=856y or 856z				
subtitle_lng_str_mv	Subtitle language codes in ISO 639-3 format with some collective language codes from ISO-639-2 /5	Yes		-	-	-		-	-	041j				
original_lng_str_mv	Language of original work in ISO 639-3 format with some collective language codes from ISO 639-2 /5	Yes		-	-	-		-	-	041[ind 1=0]a, 041h				
publication_place_txt_mv	Place of publication	No	AllFields	-	-	-		-	-	260a, 264[ind 2=1]a				
project_id_str_mv	Project ID	No		-	-	-		-	-	960a (Arto, Fennica, Helka)				
ismn_isn_mv	ISMN	No	AllFields	-	-	-		-	-	024[ind 1=2]a				
isrc_isn_mv	ISRC	No	AllFields	-	-	-		-	-	024[ind 1=0]a				
ean_isn_mv	EAN	No	AllFields	-	-	-		-	-	024[ind 1=3]a				
nbn_isn_mv	NBN	No	AllFields	-	-	-		-	-	015a				
upc_isn_mv	UPC	No	AllFields	-	-	-		-	-	024[ind 1=1]a				
category_st_mv	Category (hierarchical)	Yes		-	-	-		-	-	650ax (when enabled for the data source, SFX records only), 886[2=local, a=kategoria or a=kategoria/c/d, HILCC (when enabled for the data source)				
title_txtP	Title (unstemmed)	No	Title, AllFields	(copy of title field)	(copy of title field)	(copy of title field)		(copy of title field)	(copy of title field)	(copy of title field)				
main_date	TrieDateField version of record's main date. Can be used for e.g. date-based boosting. Make sure not to use bare "NOW" in the query (result can't be cached). Use "NOW/DAY" instead.	No		date	date	date	did->unitdate	did->unitdate	descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventDate /displayDate or descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /periodName/term	260c or 008[7:4]				
collection_t_xt_mv	Collection in searchable form	No	AllFields	(copy of collection field)	(copy of collection field)	(copy of collection field)		(copy of collection field)	(copy of collection field)	(copy of collection field)				

usage_rightstr_mv	Usage rights code. The following codes are available: usage_A = "Free use" usage_B = "Derivatives, also commercial" usage_C = "No derivatives, also commercial" usage_D = "Derivatives, non-commercial" usage_E = "No derivatives, non-commercial" usage_F = "Permission required / unknown"	Yes			rights	rights	<control>	userrestrict->p (accessrestrict->p)	administrativeMetadata/resourceWrap/resourceSet/rightsResource/rightsType/conceptID	Value based on 540c when subfield 3 is not 'metadata'			
major_genre_str_mv	Major Genre. The following codes are available: fiction nonfiction music	Yes								Value based on YKL (084 where \$2=ykl) or UDK (080) classification			
building_substr_mv	Sublocation (e.g. department)	Yes								One of the following values based on 852c if configured: 1 = "Adults" 2 = "Children and Youth" 3 = "Music" 4 = "Magazines" 5 = "Local collection" 6 = "Stacks" 7 = "Other"			
original_idstr_mv	Original record ID	No								035a when resource type from 886 is 'tietokanta' or 'data bas'			
warnings_str_mv	Metadata content processing issues	No						May be one of following (at least): * invalid end date * invalid date range	May be one of following (at least): * invalid date * invalid date range * invalid coordinates in 034 * invalid field tag 'ddd' * indicator 1 missing * indicator 2 missing * missing subfields * missing subfields in ddd * invalid subfields * invalid subfields in ddd	May be one of following (at least): * invalid date range in 008			
restricted_str	Whether use is restricted	No								'restricted' if 540 subfield 3 is 'metadata' and value is 'Ei poimintaan', or resource type from 886 is 'tietokanta' or 'databas' and 506f is not one of 'unrestricted' or 'unrestricted online access'			
format_extstr_mv	Format codes, hierarchical (see http://wiki.apache.org/solr/HierarchicalFaceting). Like format, but may contain multiple values	Yes		type	type	LearningMaterial		controlaccess->genreform or @level	descriptiveMetadata/objectClassificationWrap/objectWorkTypeWrap/objectWorkType/term	(see Marc.php : getFormat)			

building_a available_st r_mv	Like building, but only contains values that have items available.	No												
source_av ailable_st _mv	Like source_str_mv, but only contains values that have items available.	No												
work_keys _str_mv	Work identification keys. Any record containing the same key as another record is considered a version of the same work (in the FRBR sense). See Teosavainen muodostuminen (Finnish) for description of how the keys are created.	No												
mbid_str_ mv	MusicBrainz identifiers	No								An enrichment routine adds the identifiers found with existing 024 and 028 fields.				
topic_uri_s tr_mv (DE PRECATE D, BEING PHASED OUT)	Deprecated and in the process of being removed from the index as of Jan 2022. Use topic_id_str_mv instead.	No												
geographic _uri_str_m v (DEPRE CATED, BEING PHASED OUT)	Deprecated and in the process of being removed from the index as of Jan 2022. Use geographic_id_str_mv instead.	No												
author2_id _str_mv	All author identifiers	No					controlaccessname (identifier), controlaccesspersn ame(identifier), controlaccesscorpn ame(identifier) originationname (identifier), originationpersnam e(identifier), originationcorpn ame(identifier) relations->relation (relationtype='cpfre lation')(href)			Subfield 0 from 100, 110, 111, 610, 700, 710 and 711.				
topic_id_st r_mv	Topic identifiers (may include URLs and other identifiers)	No			about->thing->identifier	controlaccess /subject [@relator='aihe'] /@identifier			Subfield 0 from 600, 610, 611, 630 and 650.					
topic_add_ txt_mv	Topics added by enrichment processes	No	AllFields, \$ object, topic											
identifier_t xtP_mv	More accurate multivalued identifier field	No	Identifier						Workids, Placeids					
geographic _add_tx t_mv	Geographic topics added by enrichment processes	No	AllFields, Subject, geographic											
geographic _id_str_mv	Geographic place identifiers (may include URLs and other identifiers)	No				controlaccessgeogn ame(relator="aihe" or "alueellinen kattavuus" or no relator attribute) /@identifier		descriptiveMetadata /eventWrap/eventSet /event[eventType /term='valmistus'] /eventPlace/place /placeID, descriptiveMetadata /objectRelationWrap /subjectWrap /subjectSet/subject /subjectPlace/place /placeID, descriptiveMetadata /objectIdIdentificationW rap/repositoryWrap /repositorySet /repositoryLocation /placeID[type='prt' or 'kiinteistotunnus' or 'URI']						